













REZYSTORY TERMOMETRYCZNE

PN-EN 60751 + A2, PN-83/M-53852

Typ	Wymiary	Rezystancja nominalna (Ω)	Zakres pomiarowy ($^{\circ}\text{C}$)	Max. prąd pomiarowy (mA)	Współczynnik samopodgrzania (powietrze) ($^{\circ}\text{C}/\text{mW}$)	Czas reakcji $T_{0,9}$ (sek.)	
						w wodzie $V = 0,4 \text{ m}/\text{sek.}$	w powietrzu $V = 1 \text{ m}/\text{sek.}$
P101		Pt100 1x100	-50 ... +500	1	0,5	0,5	11
P112		Pt100 1x100	-200 ... +700	1	0,06	0,7	50
P113		Pt100 1x100	-200 ... +700	1	0,06	1,4	125
P114		Pt100 1x100	-50 ... +500	1	0,2	3	40
P501		Pt500 1x500	-50 ... +500	0,3	0,5	0,5	11
P510		Pt500 1x500	-50 ... +500	1	0,2	3	40
P901		Pt1000 1x1000	-50 ... +500	0,3	0,5	0,5	11
P910		Pt1000 1x1000	-50 ... +500	1	0,2	3	40
P122		2Pt100 2x100	-200 ... +600	1	0,06	1,4	125
P522		2Pt500 2x500	-30 ... +600	1	0,2	3	40
P922		Pt1000 2x1000	-30 ... +500	1	0,2	3	40
N112		Ni100 1x100	-50 ... +150	5	0,1	5	150

* Podano parametry rezystorów platynowych klasy B